

TOYO R888R



The Proxes R888R is Toyo's NEW street legal motorsport tyre that meets current European tyre labelling requirements for tyres used on public roads.

The Proxes R888R is designed primarily for dry conditions in competition or closed course use but retains enough void area for confident wet weather and street use.

The Proxes R888R combines the fast warm-up and progressive break-away-characteristics of the Proxes R888 with a new casing design that provides improved mid-corner grip for faster lap times and improved consistency.

FEATURES	BENEFITS
E.U. Tyre Labelling & U.S. DOT Markings	Legal for use on public roads, meeting European noise, wet grip and rolling resistance requirements
New Asymmetric Tread Pattern	Maximised dry cornering grip without compromising aquaplaning performance
"GG" Tread Compound	Fast warm-up, predictable handling and minimal tread squirm for maximised dry grip
Rayon "Super-High Turn-Up" Carcass	Improved mid-corner grip for faster lap times with increased consistency and endurance
Wide Centre Rib	Precise steering response

TYRE SIZE	TREAD	INFLATED DIM.			LOADED DIMENSION			TEST RIM	REVS PER KM.	APPROVED RIM WIDTH	
		DEPTH (mm)	O.D. (mm)	O.W. (mm)	STATIC RADIUS	STATIC WIDTH	DYNAMIC RADIUS			(INCH)	CODES (INCH)
185/60R13	80V	5.0	552	189	252	206	268	5.5	594	5.0	- 6.5
205/60R13	86V	5.0	576	209	261	228	280	6.0	569	5.5	- 7.5
185/60R14	82V	5.0	578	189	265	206	281	5.5	567	5.0	- 6.5
195/50R15	82V	5.0	577	201	267	219	280	6.0	568	5.5	- 7.0
195/55R15	85V	5.0	595	201	274	219	289	6.0	551	5.5	- 7.0
205/50R15	86W	5.0	587	214	271	233	285	6.5	559	5.5	- 7.5
225/50R15	91W	5.0	607	233	279	254	295	7.0	540	6.0	- 8.0
195/50R16	84W	5.0	602	201	279	219	292	6.0	545	5.5	- 7.0
205/45R16	83W	5.0	590	206	275	225	286	7.0	556	6.5	- 7.5
205/50R16	87W	5.0	612	214	283	233	297	6.5	536	5.5	- 7.5
225/45R16	89W	5.0	608	225	282	245	295	7.5	539	7.0	- 8.5
205/40R17	80W	5.0	596	212	280	231	289	7.5	550	7.0	- 8.0
205/45R17	84W	5.0	616	206	288	225	299	7.0	532	6.5	- 7.5
215/45R17	87W	5.0	626	213	292	232	304	7.0	524	7.0	- 8.0
225/45R17	91W	5.0	634	225	295	245	308	7.5	517	7.0	- 8.5
235/40R17	90W	5.0	620	241	289	263	301	8.5	529	8.0	- 9.5
235/45R17	94W	5.0	644	236	299	257	313	8.0	509	7.5	- 9.0
255/40R17	94W	5.0	636	260	296	283	309	9.0	516	8.5	- 10.0
225/40R18	92Y	5.0	637	230	299	251	309	8.0	515	7.5	- 9.0
235/40R18	91Y	5.0	645	241	302	263	313	8.5	508	8.0	- 9.5
245/40R18	93Y	5.0	653	248	305	270	317	8.5	502	8.0	- 9.5
255/35R18	90Y	5.0	635	260	298	283	308	9.0	516	8.5	- 10.0
265/35R18	93Y	5.0	643	271	304	295	312	9.5	510	9.0	- 10.5
275/35R18	95Y	5.0	649	278	303	303	315	9.5	505	9.0	- 11.0
295/30R18	98Y	5.0	635	301	298	328	308	10.5	516	10.0	- 11.0

235/35R19	91Y	5.0	647	241	305	263	314	8.5	507	8.0	-	9.5
265/30R19	89Y	5.0	643	271	304	295	312	9.5	510	9.0	-	10.0
295/30R19*	100Y	5.0	661	301	311	328	321	10.5	496	10.0	-	11.0
305/30R19	102Y	5.0	667	313	313	341	324	11.0	492	10.5	-	11.5
285/35R20	100Y	5.0	708	290	332	316	344	10.0	463	9.5	-	10.0
315/30R20	101Y	5.0	698	320	328	349	339	11.0	470	10.5	-	11.5