

CR28 Sport

Road Legal Tyres:

TYRE SIZE	SERVICE INDEX	RIM CHOICE	MEASURED AT		DIAMETER		SECTION		TREAD		REVOLUTIONS	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
185/60R13	80H	5.5 – 6.0	30	2.1	21.7	551	7.4	188	5.3	135	929	577
205/60R13	86H	6.0 – 6.5	30	2.1	22.7	577	7.8	198	6	152	888	552
185/70R13	86H	5.5 – 6.0	30	2.1	23.2	589	5.2	132	5.2	132	869	540
185/60R14	82H	5.5 – 6.0	30	2.1	22.7	577	7.4	188	5.3	135	888	552
195/60R14	86H	6.0-6.5	30	2.1	24.4	610	7.8	198	5.8	147	827	522
185/70 R14	88H	5.5-6.0	30	2.1	24.7	617	7.2	183	5.2	132	817	516
195/50R15	82H	6.0 – 6.5	30	2.1	22.6	574	7.7	196	6.3	160	892	554
205/50R15	86H	6.5 – 7.0	30	2.1	23	584	8.6	218	7.3	185	877	545

Motorsport — Avon — CR28

Avon Tyres Motorsport produces slick tyres in a variety of different compounds, with each compound aimed at a specific area of motorsport. This gives us the flexibility to provide highly tailored products to individuals needs. Below is a guide on compounds from hard to soft in descending order.

Note – Compound variant is only available in our slick tyre range

Remember – Softer compound does not always equal faster lap times

Stiffness	Compound	Application
Hard	A70	Ultra Hard compound for saloon car circuit slick applications.
	A29	Very Hard compound for saloon car circuit slick applications.
	A60	Medium compound for saloon car circuit slick applications.
	A30	Medium compound for classic applications.
	A37	Hard compound for sportscar, Soft compound for saloon car applications.
	A56	Hard compound for sportscar / single seater circuit slick.
	514	Medium / Hard compound for single seater and sportscar circuit slick.

A24	Medium compound for single seater, sportscar and sidecar circuit slick applications.
A11	Medium compound for single seater, sportscar and sidecar circuit slick applications.
A53	Soft compound for single seater and sidecar circuit slick applications.
A43	Hard compound for single seater circuit wet. Soft compound for sportscar.
379	Hard GT Hillclimb Compound
A49	Medium / Soft compound for rallycross, single seater circuit.
A50	Medium GT Hillclimb Compound.
A15	Very soft compound for hillclimb slick / wet single seater circuit and sidecar wet applications.
A92	Very soft compound for hillclimb slick / wet single seater circuit and sidecar wet applications.



AVON TYRES MOTORSPORT
CR28 Sport