

Crossply 15-inch

Race Tyres:

TYRE SIZE	RIM CHOICE	RIM USED	MEASURED AT		DIAMETER		SECTION		TREAD		REVOLUTIONS	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
7.0/21.5-15	5.5 – 7.5	6.00	30	2.04	22.1	561	7.4	188	7	177	912	570
7.5/21.5-15	6.0 – 8.0	6.00	30	2.04	22.2	563	7.8	198	7.2	182	908	568
8.0/21.5-15	6.5 – 8.5	7.50	30	2.04	21.8	553	8.8	224	7.8	198	925	578
8.7/21.5-15	7.5 – 9.0	8.00	30	2.04	22.1	561	9.7	246	8.4	213	912	570
9.5/21.5-15	8.0 – 10.0	10.00	30	2.04	21.85	554	10.65	271	9.5	241	923	577
10.0/21.5-15	8.5 – 11.0	10.00	30	2.04	21.85	554	11	279	10	254	923	577
10.7/21.5-15	9.0 – 11.0	10.00	30	2.04	21.85	554	11.3	287	10.6	269	923	577
8.0/22.5-15	6.5 – 7.5	7.00	30	2.04	22.45	570	8.95	227	7.75	196	898	561
6.5/23.0-15	6.0 – 7.5	6.00	30	2.04	23	584	7.55	192	6.5	165	877	548
7.0/23.0-15	6.5 – 8.0	7.00	30	2.04	23.1	586	7.95	202	6.9	175	873	546
7.5/23.0-15	7.0 – 8.5	8.00	30	2.04	22.8	579	8.5	216	7.4	187	884	552
10.5/23.0-15	10.0 – 12.0	11.00	30	2.04	23.55	598	11.95	304	10.3	261	856	535
8.5/23.5-15	7.0 – 9.5	8.50	30	2.04	23.6	599	9.6	244	8.8	223	854	534
9.0/23.5-15	7.0 – 10.0	8.50	30	2.04	23.6	599	9.9	251	9.3	236	854	534
9.1/23.5-15	8.0 – 9.5	8.50	30	2.04	23.55	598	9.88	251	8.5	215	856	535

11.0/23.5-15	10.0 – 12.0	11.00	30	2.04	23.3	591	12.1	307	11.3	287	865	541
12.5/23.5-15	11.0 – 13.5	12.00	30	2.04	23.3	591	13.3	338	12.7	322	865	541
9.0/25.0-15	9.0 – 11.0	10.0	30	2.1	24.75	629	10.1	257	8.9	226	815	506
9.5/25.0-15	9.0 – 11.0	10.00	30	2.04	24.75	628	11.7	297	9.25	234	815	509
11.0/25.0-15	10.0 – 12.0	12.00	30	2.04	24.7	627	13.6	345	11.3	287	816	510
13.0/25.0-15	11.5 – 14.0	14.00	30	2.04	24.8	629	15.4	391	13.2	335	813	508
15.0/26.0-15	15.0 – 17.0	16.00	30	2.04	25.75	654	17.4	442	15	381	783	489
16.2/26.0-15	16.0 – 18.0	16.00	30	2.04	25.8	655	17.9	455	16.3	414	782	489
12.5/27.0-15	11.5 – 14.5	13.00	30	2.04	27	685	15.25	387	12.5	317	747	467
14.0/27.0-15	13.0 – 16.0	15.00	30	2.04	27.1	688	16.7	424	14	355	744	465
16.0/27.0-15	15.0 – 18.0	16.00	30	2.04	27.5	698	16.8	427	16.1	408	733	458

Motorsport — Avon — Crossply 15

Avon Tyres Motorsport produces slick tyres in a variety of different compounds, with each compound aimed at a specific area of motorsport. This gives us the flexibility to provide highly tailored products to individuals needs. Below is a guide on compounds from hard to soft in descending order.

Note – Compound variant is only available in our slick tyre range

Remember – Softer compound does not always equal faster lap times

Stiffness	Compound	Application
Hard	A70	Ultra Hard compound for saloon car circuit slick applications.
	A29	Very Hard compound for saloon car circuit slick applications.
	A60	Medium compound for saloon car circuit slick applications.
	A30	Medium compound for classic applications.
	A37	Hard compound for sportscar, Soft compound for saloon car applications.

A56	Hard compound for sportscar / single seater circuit slick.
514	Medium / Hard compound for single seater and sportscar circuit slick.
A24	Medium compound for single seater, sportscar and sidecar circuit slick applications.
A11	Medium compound for single seater, sportscar and sidecar circuit slick applications.
A53	Soft compound for single seater and sidecar circuit slick applications.
A43	Hard compound for single seater circuit wet. Soft compound for sportscar.
379	Hard GT Hillclimb Compound
A49	Medium / Soft compound for rallycross, single seater circuit.
A50	Medium GT Hillclimb Compound.
A15	Very soft compound for hillclimb slick / wet single seater circuit and sidecar wet applications.
A92	Very soft compound for hillclimb slick / wet single seater circuit and sidecar wet applications.



AVON TYRES MOTORSPORT
15-Inch Diameter